

API Casing List Sizes, Masses, Wall Thickness, Grade and Application End-Finish

Labels		Outside Diameter	Nominal Linear mass T&C	Wall thickness	Outside Diameter	Nominal Linear mass T&C	Wall thickness	Types of End-Finish							
1	2	D mm	kg/m	t mm	D in	lb/ft	t in	H40	J55 K55	M65	L80 R95	N80 Type 1.Q	C90 T95	C110	P110
4 -1/2	9.50	114.30	14.14	5.21	4.500	9.50	0.205	PS	PS	PS	-	-	-	-	-
4 -1/2	10.50	114.30	15.63	5.69	4.500	10.50	0.224	-	PSB	PSB	-	-	-	-	-
4 -1/2	11.60	114.30	17.26	6.35	4.500	11.60	0.250	-	PSLB	PLB	PLB	PLB	PLB	P	PLB
4 -1/2	13.50	114.30	20.09	7.37	4.500	13.50	0.290	-	-	PLB	PLB	PLB	PLB	P	PLB
4 -1/2	15.10	114.30	22.47	8.56	4.500	15.10	0.337	-	-	-	-	-	-	-	-
5	11.50	127.00	17.11	5.59	5.000	11.50	0.220	-	PS	PS	-	-	-	-	-
5	13.00	127.00	19.35	6.43	5.000	13.00	0.253	-	PSLB	PSLB	-	-	-	-	-
5	15.00	127.00	22.32	7.52	5.000	15.00	0.296	-	PSLB	PLB	PLB	PLB	PLB	P	PLB
5	18.00	127.00	26.79	9.19	5.000	18.00	0.362	-	-	PLB	PLB	PLB	PLB	P	PLB
5	21.40	127.00	31.85	11.10	5.000	21.40	0.437	-	-	PLB	PLB	PLB	PLB	P	PLB
5	23.20	127.00	34.53	12.14	5.000	23.20	0.478	-	-	-	PLB	PLB	PLB	P	PLB
5	24.10	127.00	35.86	12.70	5.000	24.10	0.500	-	-	-	PLB	PLB	PLB	P	PLB

P = Plain End, S = Short Round Thread, L = Long Round Thread, B = Buttress Thread

Above data are only for reference and HMTL don't take any liability for the same.