

API External-Upset Tubing Coupling-Dimensions, Tolerances and Masses

Labels	Outside Diameter D	Outside Diameter				Minimum Length NL	Diameter of Recess Q		Width of Bearing Face, Regular b		Maximum Bearing Face Diameter B				Mass				
		Regular W		Special Clearance WC			mm	in	mm	in	Regular with Special Bevel		Special Clearance		Regular		Special Clearance		
in	mm	mm	in	mm	in	mm					in	mm	in	mm	in	mm	in	mm	in
1.050	26.67	42.16	1.660	-	-	82.55	3 1/4	35.00	1.378	2.38	3/32	37.80	1.488	-	-	0.38	0.84	-	-
1.315	33.40	48.26	1.900	-	-	88.90	3 1/2	38.89	1.531	2.38	3/32	42.77	1.684	-	-	0.57	1.26	-	-
1.660	42.16	55.88	2.200	-	-	95.25	3 3/4	47.63	1.875	3.18	1/8	50.95	2.006	-	-	0.68	1.49	-	-
1.900	48.26	63.50	2.500	-	-	98.42	3 7/8	54.76	2.156	3.18	1/8	58.34	2.297	-	-	0.84	1.85	-	-
2-3/8	60.32	77.80	3.063	73.91	2.910	123.82	4 7/8	67.46	2.656	3.97	5/32	71.83	2.888	69.90	2.752	1.55	3.43	1.07	2.35
2-7/8	70.02	93.17	3.668	87.88	3.460	133.35	5 1/4	80.16	3.156	5.56	7/32	85.88	3.381	83.24	3.277	2.40	5.30	1.55	3.42
3-1/2	88.90	114.30	4.500	106.70	4.180	146.05	5 3/4	96.85	3.813	6.35	1/4	104.78	4.125	100.71	3.965	4.10	9.03	2.38	5.24
4	101.60	127.00	5.000	-	-	152.40	6	109.55	4.313	6.35	1/4	117.48	4.625	-	-	4.82	10.63	-	-
4-1/2	114.30	141.30	5.563	-	-	158.75	6 1/4	122.25	4.813	6.35	1/4	130.96	5.156	-	-	6.05	13.33	-	-

Tolerance on out side diameter W : +/- 1%

Tolerance on out side diameter WC : +/- 0.015 inch

Above data are only for reference and HMTL don't take any liability for the same.