

## API Non-Upset Tubing Coupling-Dimensions, Tolerances and Masses

Labels	Outside Diameter	Outside Diameter W		Minimum Length NL		Diameter of Recess Q		Width of Bearing Face b		Maximum Bearing Face Diameter, Special Bevel Bf		Mass	
		mm	in	mm	in	mm	in	mm	in	mm	in	kg	lb
1.050	26.67	33.35	1.313	80.96	3 3/16	28.27	1.113	1.59	1/16	30.00	1.181	0.23	0.51
1.315	33.40	42.16	1.660	82.55	3 1/4	35.00	1.378	2.38	3/32	37.80	1.488	0.38	0.84
1.660	42.16	52.17	2.054	88.90	3 1/2	43.76	1.723	3.18	1/8	47.17	1.857	0.59	1.29
1.900	48.26	55.88	2.200	95.25	3 3/4	49.86	1.963	1.59	1/16	52.07	2.050	0.56	1.23
2-3/8	60.32	73.02	2.875	107.95	4 1/4	61.93	2.438	4.76	3/16	66.68	2.626	1.28	2.82
2-7/8	70.02	88.90	3.500	130.18	5 1/8	74.63	2.938	4.76	3/16	80.98	3.188	2.34	5.15
3-1/2	88.90	107.95	4.250	142.88	5 5/8	90.50	3.563	4.76	3/16	98.42	3.875	3.71	5.17
4	101.60	120.65	4.750	146.05	5 3/4	103.20	4.063	4.76	3/16	111.12	4.375	4.35	9.58
4-1/2	114.30	132.08	5.200	155.58	6 1/8	115.90	4.563	4.76	3/16	123.19	4.850	4.89	10.77

Above data are only for reference and HMTL don't take any liability for the same.