

External upset Tubing Dimensions for API Connections, Groups 1, 2 and 3

Labels		Outside Diameter	Nominal Linear mass threaded and coupled		Upset							
					Outside Diameter D4		Length from end of pipe to start of taper (Leu)		Length from end of pipe to end of taper (La)		Length from end of pipe to start of body (Lb)	
1	2	D mm	lb/ft	kg/m	in +0.0625/0	mm +1.59/0	in 0 / -1	mm +0 / -25.4	in	mm	in max	mm max
1.050	1.20	26.67	1.200	1.79	1.315	33.40	2 3/8	60.320	-	-	-	-
1.050	1.54	26.67	1.540	2.29	1.315	33.40	2 3/8	60.320	-	-	-	-
1.315	1.80	33.40	1.800	2.68	1.469	37.31	2 1/2	63.500	-	-	-	-
1.315	2.24	33.40	2.240	3.33	1.469	37.31	2 1/2	63.500	-	-	-	-
1.660	2.40	42.16	2.400	3.57	1.812	46.02	2 5/8	66.680	-	-	-	-
1.660	3.07	42.16	3.070	4.57	1.812	46.02	2 5/8	66.680	-	-	-	-
1.900	2.90	48.26	2.900	4.32	2.094	53.19	2 11/16	68.260	-	-	-	-
1.900	3.70	48.26	3.730	5.55	2.094	53.19	2 11/16	68.260	-	-	-	-
2 - 3/8	4.70	60.32	4.700	6.99	2.594	65.89	4.000	101.600	6.000	152.40	10.000	254.00
2 - 3/8	5.95	60.32	5.950	8.85	2.594	65.89	4.000	101.600	6.000	152.40	10.000	254.00
2 - 3/8	7.45	60.32	7.450	11.09	2.594	65.89	4.000	101.600	6.000	152.40	10.000	254.00
2- 7/8	6.50	73.02	6.500	9.67	3.094	78.59	4 1/4	107.950	6 1/4	158.75	10 1/4	260.35
2- 7/8	7.90	73.02	7.900	11.76	3.094	78.59	4 1/4	107.950	6 1/4	158.75	10 1/4	260.35
2- 7/8	8.70	73.02	8.700	12.95	3.094	78.59	4 1/4	107.950	6 1/4	158.75	10 1/4	260.35
2- 7/8	9.45	73.02	9.450	14.06	3.094	78.59	4 1/4	107.950	6 1/4	158.75	10 1/4	260.35
3-1/2	9.30	88.90	9.300	13.84	3.750	95.25	4 1/2	114.3	6 1/2	165.10	10 1/2	266.70
3-1/2	12.95	88.90	12.950	19.27	3.750	95.25	4 1/2	114.3	6 1/2	165.10	10 1/2	266.70
4	11.00	101.60	11.000	16.37	4.250	107.95	4 1/2	114.3	6 1/2	165.10	10 1/2	266.70
4 - 1/2	12.75	114.30	12.750	18.97	4.750	120.65	4 3/4	120.65	6 3/4	171.45	10 3/4	273.05

Above data are only for reference and HMTL don't take any liability for the same.